

QBCR.E161223 Outlet and Junction Boxes for Use in Hazardous Locations

Page Bottom

Outlet and Junction Boxes for Use in Hazardous Locations

See General Information for Outlet and Junction Boxes for Use in Hazardous Locations

TECNASA E161223

Cra. 32 No. 22B-66 Bogota, DC COLOMBIA

Class I, Groups C and D; Class II, Groups E, F and G.

Conduit boxes threaded for rigid conduit connection, Series SX7E outlet box Cat. Nos. SX7E-644, -664, -666, -864, -866, -883, -884, -888, SX7E-A66, -AA6, -C56, -FC6, -GC6, -GC8, -GE9, -GF6, -GG6, -IC8, -IIC, -KK8, -OCC, -OF6, -SG8, -SGD, -XCD, conduit sizes 1/2 through 4 in.

Class I, Group D; Class I, Groups E, F and G.

Conduit box threaded for rigid conduit connection, Cat. No. SXEGJ421, conduit size 3/4 in.

Last Updated on 2008-11-04

Questions? Print this page Terms of Use Page Top

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a nonmisleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "@ 2016 UL LLC".