

FTRV.E161224 **Enclosures for Use in Hazardous Locations**

Page Bottom

Enclosures for Use in Hazardous Locations

See General Information for Enclosures for Use in Hazardous Locations

TECNASA E161224

Cra. 32 No. 22B-66 Bogota, DC COLOMBIA

Class I, Groups C and D; Class II, Groups E, F and G.

Series SX9 GUB, Cat. No. SX9GUB may be followed by -D, -DW or -W, followed by -1, -2 or -3, may be followed by A, followed by -1, -2, -3, -4, -10, -12, -16, -17, -27 or -35, followed by -1, -2, -3, -4, -5, -6, -7, -8, -9 and/or -10.

Series SXE, Cat. No. SXE, followed by -1/2 or -3.

Series SX7E, Cat. No. SX7E, followed by -FC6, -GC6, -GC8, -GE9, -GF6, -GG6, -IC8, -IIC, -KK8, -OCC, -OF6, -SG8, -SGD and -XCD.

Series SX7E enclosures, Cat. Nos. SX7E-644, -664, -666, -864, -866, -883, -884, -888, -A66, -AA6, -C56 for use in Class I, Groups C and D; Class II, Groups E, F and G Hazardous Locations. Conduit sizes 1/2 through 4 in. NPT.

Last Updated on 2013-06-26

Print this page Terms of Use Questions? Page Top

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a nonmisleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".